
BIOFLEX ULTRA

PTFE Hose for Pharmaceutical and Biotech Fluids Transfer

Very Flexible, yet Kink Resistant - Smooth Bore for Uninterrupted Fluid Flow and Ease of Cleaning



BIOFLEX ULTRA HOSE SPECIFICATIONS

HOSE BORE SIZE RANGE -

3/8" (10MM) UP TO 3" (80MM)

HOSE LENGTHS -

UP TO 30 METRES (100 FEET) UP TO 2", 18 METRES (60 FEET) UP TO $2^{1}/2$ ", 15 METRES (50 FEET) UP TO 3"

TEMPERATURE LIMITS -

SS Braided Hose -73°C (-100°F) TO +260°C (+500°F)

EPDM Rubber Covered Hose -40°C (-40°F) TO +150°C (+302°F)

Silicone Rubber Covered Hose -73°C (-100°F) TO +204°C (+400°F)

WORKING PRESSURE RATINGS -

FOR SS BRAIDED AND RUBBER COVERED HOSE 80 BAR (1160 PSI) FOR 3/8" BORE HOSE, UP TO 30 BAR (435 PSI) FOR 2" BORE HOSE

VACUUM LIMITATIONS -

VACUUM RESISTANT TO -0.9BAR FOR ALL SIZES

END FITTINGS Non-Lined, or PTFE Lined and Flared design for:
ANSI 150, DIN AND JIS SWIVEL FLANGE FITTINGS, CAM & GROOVE
FITTINGS, SANITARY TRICLAMP FITTINGS, DIN 11851 AND SMS
HYGIENIC FITTINGS, I-LINE FITTINGS AND DIP PIPES

END FITTINGS Non-Lined design for:

BSP, NPT AND JIC THREADED FITTINGS, AND RJT FITTINGS

BRAID DESIGN OPTIONS -

STAINLESS STEEL WIRE OR POLYPROPYLENE YARN BRAIDS ARE STANDARD, WITH HASTELLOY OR PVDF BRAIDS TO SPECIAL ORDER

EXTERNAL COVER OPTIONS -

BLUE (GRADE RC) OR BLACK (GRADE BK) EPDM RUBBER COVER, OR CLEAR SILICONE RUBBER COVER (GRADE SI)

APPROVALS -


ISO 9001, EN16643, TS16949, ISO 14001, FDA (MATERIALS), USP 6, ATEX, 3-A SANITARY STANDARDS, 3.1 TRACEABILITY, GRADE BK FIREPROOF TO BS5173, (EU) 10/2011

FOR THE FULL BIOFLEX ULTRA HOSE BROCHURE PLEASE VISIT - WWW.AFLEX-HOSE.COM

UK 44 (0)1422 317200 USA 215 766 1455

BIOFLEX ULTRA

PTFE Hose for Pharmaceutical and Biotech Fluids Transfer



UK

Spring Bank Industrial Estate 32 Appletree Lane Watson Mill Lane Pipersville Sowerby Bridge Halifax West Yorkshire, HX6 3BW

Tel: +44 (0) 1422 317200 Tel: 215 - 766 - 1455

USA

Bucks County Pa 18947

Fax: +44 (0) 1422 836000 Fax: 215 - 766 - 1688



