
# **SMOOTHBORE**

PTFE Hose for Automotive and General Purpose Applications

A High Temperature and Pressure Resistant, Smooth Bore Hose compatible with all Automotive Fluids



# SMOOTHBORE HOSE SPECIFICATIONS

#### **HOSE BORE SIZE RANGE-**

Standard Wall and Heavy Wall 1/8" (3MM) UP TO 1" (25MM)
Medium Wall ('Dash Sizes')

-3 (3.5MM BORE) TO -16 (26.4MM BORE)

### **HOSE LENGTHS -**

-3 SIZE 200 METRES (650 FEET) TO -16 SIZE 40 METRES (130 FEET) CUT LENGTHS AND PREFORMED LENGTHS AVAILABLE

# **TEMPERATURE LIMITS -**

FROM -73°C (-100°F) UP TO +260°C (+500°F), DEPENDING ON PRESSURE

# **WORKING PRESSURE RATINGS -**

-3 = 350 BAR (5000 PSI) TO -16 = 80 BAR (1150 PSI), FOR TEMPERATURES UP TO 150°C (300°F)

# **VACUUM LIMITATIONS -**

VACUUM RESISTANT TO -0.9BAR FOR HEAVY WALL HOSE IN SIZES UP TO  $^3/\epsilon^{\prime\prime}$  (10MM)

#### **END FITTINGS -**

BSPT AND NPT MALE AND FEMALE, BSP AND NPSM 60° CONE SEAT AND FLAT SEAT FEMALE UNIONS, JIC THREADED MALE AND FEMALE FITTINGS, STANDPIPE FITTINGS AND MANY MORE

#### ALTERNATIVE DESIGN OPTIONS (to special order) -

- DOUBLE BRAID OR 'HIGH PACK' BRAID FOR INCREASED PRESSURE RESISTANCE, HIGH PRESSURE GAS GRADE
- PVC, NYLON II, SARLINK AND HYTREL PLASTIC COVERS OVER BRAID WITH PRINTING. DIFFERENT COLOURS AND OTHER PLASTIC COVERS ARE ALSO AVAILABLE.
- FOR LARGER BORE SIZE WHERE IMPROVED FLEXIBILITY IS NEEDED, HYPERLINE FX HOSE IS RECOMMENDED.

# **APPROVALS** -


ISO 9001, TS16949, ISO 14001, EN16643, FDA (MATERIALS), USP 6, SAE J1401 & J1737, 3.1 TRACEABILITY

FOR THE FULL SMOOTHBORE BROCHURE PLEASE VISIT - WWW.AFLEX-HOSE.COM

UK +44 (0)1422 317200 USA 215 766 1455

# SMOOTHBORE

PTFE Hose for Automotive and General Purpose Applications



# UK

Spring Bank Industrial Estate 32 Appletree Lane Watson Mill Lane Sowerby Bridge Halifax West Yorkshire, HX6 3BW

Tel: +44 (0) 1422 317200 Fax: +44 (0) 1422 836000 Fax: 215 - 766 - 1688

#### USA

Pipersville Bucks County Pa 18947

Tel: 215 - 766 - 1455



